

**CLAIM AMENDMENTS**

1 1 (currently amended): A method of using a pull cord operatively connected to a  
2 rotatable shaft to reversibly rotate the shaft, the method comprising the steps:

3 (a) pulling a pull cord in a first direction, thereby rotating a first shaft in a  
4 selected direction and converting rotation of the first shaft into rotation of a second shaft in  
5 a first direction;

6 (b) retracting the pull cord; and

7 (c) pulling the pull cord in a second direction, different from the first direction  
8 of the pull cord, thereby rotating the first shaft in the selected direction and converting  
9 rotation of the first shaft into rotation of the second shaft in a second direction, opposite the  
10 first direction of the shaft.

1 2 (currently amended): A method of using a pull cord operatively connected to a  
2 rotatable shaft having a load attached thereto to selectively rotate the shaft in opposite  
3 directions and thereby position the load, the method comprising the steps:

4 (a) pulling a pull cord in a direction selected from first and second, different  
5 pull directions, thereby rotating a first shaft in a selected direction and converting rotation  
6 of the first shaft in the selected direction into rotation of a second shaft in a direction selected  
7 from first and second, opposite directions of rotation, the first and second directions of  
8 rotation being selected by the first and second pull directions, respectively;

9 (b) returning the pull cord; and

10 (c) repeating steps (a) and (b).

USSN: 10/679,937  
Art Unit: 3634  
Examiner: Johnson, Blair M.

AMENDMENT  
Dated: 02 August 2006  
Page: 3 of 11

1           3 (currently amended): A reversible pull cord mechanism, comprising:  
2           first and second rotatable shafts;  
3           a pull cord means operatively connected to the first shaft and to the second  
4 shaft ~~and including a pull cord~~ for rotating the first shaft in a selected direction when the pull  
5 cord is pulled;  
6           means operatively connected to the pull cord ~~means~~ and responsive to pulling  
7 the pull cord in different directions for rotating the first shaft in ~~a selected~~ the selected  
8 direction; and  
9           means operatively connected to the first shaft and to the second shaft and  
10 responsive to pulling the pull cord in two of said different directions for converting rotation  
11 of the first shaft in the selected direction into rotation of the second shaft in two opposite  
12 directions, respectively.

1           4 (currently amended): A reversible pull cord mechanism, comprising:  
2           first and second rotatable shafts;  
3           ~~pull cord means including~~ a pull cord ~~and~~ operatively connected to the first  
4 shaft for rotating the first shaft in a selected direction when the pull cord is pulled;  
5           means for retracting the pull cord;  
6           means for converting rotation of the first shaft in the selected direction into  
7 rotation of the second shaft, said converting means being settable in first and second  
8 conditions for converting rotation of the first shaft in the selected direction into rotation of  
9 the second shaft in first and second different directions, respectively ; and  
10           means responsive to pulling movement of the pull cord in first and second  
11 different directions for selectively setting the converting means in the first and second  
12 conditions, respectively, as the pull cord is pulled.

USSN: 10/679,937  
Art Unit: 3634  
Examiner: Johnson, Blair M.

AMENDMENT  
Dated: 02 August 2006  
Page: 4 of 11

1           5 (currently amended): A reversible pull cord mechanism, comprising:  
2           a retractable pull cord mechanism comprising: a first rotatable shaft; a pulley  
3           operatively connected to the first rotatable shaft for rotating the first rotatable shaft; ~~pull cord~~  
4           ~~means including~~ a pull cord wrapped around the pulley for rotating the pulley and the first  
5           rotatable shaft when the pull cord is pulled away from the pulley; and means operatively  
6           connected to the first rotatable shaft for rewinding the pull cord when the pull cord is  
7           released;  
8           a second rotatable shaft operatively connected to the first rotatable shaft for  
9           rotating the second rotatable shaft when the first rotatable shaft rotates;  
10          ~~shifting~~ means adapted for positioning in first and second positions for  
11          converting single direction rotation of the first rotatable shaft into rotation of the second  
12          rotatable shaft in first and second different directions; and  
13          ~~connecting~~ means connecting the pull cord ~~means~~ to the ~~shifting~~ converting  
14          means for setting the ~~shifting~~ converting means in said first and second positions in response  
15          to the pull cord being pulled in first and second different directions.

1           6 (currently amended): A reversible rotation pull cord mechanism, comprising:  
2           a retractable pull cord mechanism, comprising: a first rotatable shaft; a pulley  
3           operatively connected to the first rotatable shaft for rotating the first rotatable shaft; ~~pull cord~~  
4           ~~means, including~~ a pull cord wrapped around the pulley for rotating the pulley and the first  
5           rotatable shaft when the pull cord is pulled away from the pulley; and rewind means  
6           operatively connected to the first rotatable shaft for rewinding the pull cord when the pull  
7           cord is released;

USSN: 10/679,937  
Art Unit: 3634  
Examiner: Johnson, Blair M.

**AMENDMENT**  
Dated: 02 August 2006  
Page: 5 of 11

8 a transmission including a second rotatable shaft operatively connected to the  
9 first rotatable shaft for rotating the second shaft when the first shaft rotates; the transmission  
10 further comprising shifting means adapted for being positioned in at least first and second  
11 positions for converting single direction rotation of the first rotatable shaft into rotation of  
12 the second rotatable shaft in first and second different directions; and  
13 connecting means connecting the pull cord ~~means~~ to the shifting means for setting the  
14 transmission in said first and second positions in response to the pull cord being pulled in  
15 first and second different directions.

1 7 (currently amended): The reversible pull cord mechanism of claim 6, wherein:  
2 the transmission comprises: a first gear operatively mounted on the first  
3 rotatable shaft for rotating therewith in a first direction; a second gear meshed with the first  
4 gear for rotating in a second direction, opposite the first direction; and a third, output gear;  
5 and wherein

6 the shifting means comprises fourth and fifth gears; a movable shaft mounting  
7 the fourth and fifth gears at spaced apart locations along said movable shaft with the fifth  
8 gear maintained meshed with the third, output gear; said movable shaft being mounted for  
9 arcuate movement between said first position, at which the fourth gear meshes with the first  
10 gear for rotating the fifth gear with the first gear and said second position, at which the fourth  
11 gear meshes with the second gear for rotating the fifth gear with the second gear; and  
12 wherein

13 said connecting means operatively connects the pull cord ~~means~~ to said  
14 movable shaft for moving said movable shaft to the said first and second positions.

USSN: 10/679,937  
Art Unit: 3634  
Examiner: Johnson, Blair M.

AMENDMENT  
Dated: 02 August 2006  
Page: 6 of 11

1           8 (original): The reversible pull cord mechanism of claim 7, said connecting means  
2 further comprising: first spring means comprising a first arm or section mounted proximate  
3 the shifting means for rotating movement; a second arm or section mounted proximate one  
4 end to and extending from the first arm and mounted proximate a second end to the movable  
5 shaft of the shifting means for moving the movable shaft between and to said first and second  
6 positions upon rotation of the first arm; and a third arm mounted to and extending from the  
7 first arm for rotating the first arm, thereby pivoting the second arm and moving the movable  
8 shaft between and to said first and second positions.

1           9 (currently amended): The reversible rotation pull cord mechanism of claim 6,  
2 wherein

3           the transmission comprises: a first gear operatively mounted on the first  
4 rotatable shaft for rotating therewith in a first direction; a second gear meshed with the first  
5 gear for rotating in a second direction, opposite the first direction; and a third, output gear;  
6 and wherein

7           the shifting means of the transmission comprises fourth and fifth gears; a  
8 movable shaft mounting the fourth and fifth gears at spaced apart locations along said  
9 movable shaft with the fifth gear maintained meshed with the third, output gear; said  
10 movable shaft being mounted for arcuate movement among and to said first position, in  
11 which the fourth gear meshes with the first gear for rotating the fifth gear with the first gear,  
12 said second position, in which the fourth gear meshes with the second gear for rotating the  
13 fifth gear with the second gear, and a third, neutral position between said first and second  
14 positions at which the fourth gear is disengaged from the first and second gears; and wherein

USSN: 10/679,937  
Art Unit: 3634  
Examiner: Johnson, Blair M.

**AMENDMENT**  
Dated: 02 August 2006  
Page: 7 of 11

15           said connecting means operatively connects the pull cord ~~means~~ to said  
16 movable shaft for moving said movable shaft among and to said first, second and third  
17 positions.

1           10 (original): The reversible pull cord mechanism of claim 9, said connecting means  
2 further comprising:

3           first spring means comprising a first arm or section mounted proximate the  
4 shifting means for rotating movement; a second arm or section mounted proximate one end  
5 to and extending from the first arm and mounted proximate a second end to the movable  
6 shaft of the shifting means for moving the movable shaft among and to said three positions  
7 upon rotation of the first arm; and a third arm mounted to and extending from the first arm  
8 for rotating the first arm, thereby pivoting the second arm and moving the movable shaft  
9 among and to said three positions; and the third arm having an aperture therein receiving the  
10 pull cord in sliding engagement such that pulling the pull cord in first and second directions  
11 moves the movable shaft to said first and second positions; and

12           second spring means mounted proximate the first spring means and having a  
13 detent positioned such that when the pull cord is released, the detent releasably engages the  
14 first spring means and positions the first spring means in said neutral third position, and  
15 disengages from the first spring when the pull cord is pulled in the first or second direction.

1           11 (currently amended): A pull cord-operated retractable cover system, comprising:

2           (1) a cover system comprising: a housing; a plurality of rotatable pulleys  
3 mounted on or to the housing; a cover; cords wound around the pulleys and connected  
4 to the cover for extending the cover from the housing and retracting the cover to the  
5 housing; and

USSN: 10/679,937  
Art Unit: 3634  
Examiner: Johnson, Blair M.

AMENDMENT  
Dated: 02 August 2006  
Page: 8 of 11

(2) a reversible pull cord mechanism, comprising:

( a ) retractable pull cord means comprising: a first rotatable shaft; a pulley operatively connected to the first rotatable shaft for rotating the first rotatable shaft; a pull cord wrapped around the pulley for rotating the pulley and the first rotatable shaft when the pull cord is pulled away from the pulley; and means operatively connected to the first rotatable shaft for rewinding the pull cord when the pull cord is released;

( b ) a transmission including a second rotatable shaft and being operatively connected to the first rotatable shaft for rotating the second rotatable shaft when the first rotatable shaft rotates; the transmission further comprising shifting means adapted for positioning in first and second positions for converting single direction rotation of the first rotatable shaft into rotation of the second rotatable shaft in first and second different directions; and

( c ) means connecting the pull cord means to the shifting means and setting the transmission in said first and second positions in response to the pull cord being pulled in first and second different directions.

12 (original): The cover system of claim 11, wherein:

the transmission comprises: a first gear operatively mounted on the first rotatable shaft for rotating therewith in a first direction; a second gear meshed with the first gear for rotating in a second direction, opposite the first direction; a third, output gear; and wherein:

the shifting means of the transmission comprises fourth and fifth gears; a movable shaft mounting the fourth and fifth gears at spaced apart locations along said movable shaft with the fifth gear maintained meshed with the third, output gear; said

USSN: 10/679,937  
Art Unit: 3634  
Examiner: Johnson, Blair M.

AMENDMENT  
Dated: 02 August 2006  
Page: 9 of 11

9 movable shaft being mounted for arcuate movement between said first position, in which the  
10 fourth gear meshes with the first gear for rotating the fifth gear with the first gear and said  
11 second position, in which the fourth gear meshes with the second gear for rotating the fifth  
12 gear with the second gear; and wherein:

13 said connecting means operatively connects the pull cord means to said  
14 movable shaft for moving said movable shaft to said first and second positions.

1 13 (original): The cover system of claim 12, said connecting means further  
2 comprising first spring means comprising a first arm or section mounted proximate the  
3 shifting means for rotating movement; a second arm or section mounted proximate one end  
4 to and extending from the first arm and mounted proximate a second end to said movable  
5 shaft of the shifting means for moving said movable shaft between and to said first and  
6 second positions upon rotation of the first arm; and a third arm mounted to and extending  
7 from the first arm for rotating the first arm, thereby pivoting the second arm and moving the  
8 movable shaft between and to said two positions.

1 14 (original): The cover system of claim 11, wherein:

2 the transmission comprises: a first gear operatively mounted on the first  
3 rotatable shaft for rotating therewith in a first direction; a second gear meshed with the first  
4 gear for rotating in a second direction, opposite the first direction; and a third, output gear;  
5 and wherein:

6 the shifting means of the transmission comprises fourth and fifth gears; a  
7 movable shaft mounting the fourth and fifth gears at spaced apart locations along said  
8 movable shaft with the fifth gear maintained meshed with the third, output gear; said  
9 movable shaft being mounted for arcuate movement among and to said first position, in



USSN: 10/679,937  
Art Unit: 3634  
Examiner: Johnson, Blair M.

AMENDMENT  
Dated: 02 August 2006  
Page: 10 of 11

10 which the fourth gear meshes with the first gear for rotating the fifth gear with the first gear,  
11 said second position, in which the fourth gear meshes with the second gear for rotating the  
12 fifth gear with the second gear, and a third, neutral position between said first and second  
13 positions in which the fourth gear is disengaged from the first and second gears; and wherein:

14 said connecting means operatively connects the pull cord means to said  
15 movable shaft for moving the movable shaft among and to said first, second and third  
16 positions.

1 15 (original): The cover system of claim 14, said connecting further comprising:

2 first spring means comprising a first arm or section mounted proximate the  
3 shifting means for rotating movement; a second arm or section mounted proximate one end  
4 to and extending from the first arm and mounted proximate a second end to the movable  
5 shaft of the shifting means for moving the movable shaft among and to said three positions  
6 upon rotation of the first arm; and a third arm mounted to and extending from the first arm  
7 for rotating the first arm, thereby pivoting the second arm and moving said movable shaft  
8 among and to said three positions; and the third arm having an aperture therein receiving the  
9 pull cord in sliding engagement such that pulling the pull cord in first and second directions  
10 moves said movable shaft to said first and second positions; and

11 second spring means mounted proximate the first spring means and having a  
12 detent positioned such that when the pull cord is released, the detent releasably engages the  
13 first spring means and positions the first spring means in said neutral third position, and  
14 disengages from the first spring when the pull cord is pulled in the first or second direction.